

SELF-IMPROVING VISION-LANGUAGE-ACTION MODELS WITH DATA GENERATION VIA RESIDUAL RL

Wenli Xiao^{1,2†}, Haotian Lin^{2†}, Andy Peng^{1,3}, Haoru Xue^{1,3}, Tairan He^{1,2}, Yuqi Xie¹,
Fengyuan Hu¹, Jimmy Wu¹, Zhengyi Luo¹, Linxi “Jim” Fan¹, Guanya Shi², Yuke Zhu^{1,4}
¹NVIDIA, ²CMU, ³UC Berkeley, ⁴UT Austin, [†]Equal Contributions

ABSTRACT

Supervised fine-tuning (SFT) has become the de facto post-training strategy for large vision-language-action (VLA) models, but its reliance on costly human demonstrations limits scalability and generalization. We propose Probe, Learn, Distill (**PLD**), a three-stage plug-and-play framework that improves VLAs through residual reinforcement learning (RL) and distribution-aware data collection. In Stage 1 (*specialist acquisition*), we freeze the VLA backbone and train lightweight residual actors via off-policy RL. These specialists take over in states where the base policy fails, thereby probing failure regions of the VLA generalist. In Stage 2 (*data collection*), we employ a hybrid rollout scheme that biases residual interventions toward states frequently visited by the base policy, aligning collected trajectories with the generalist’s deployment distribution while capturing recovery behaviors. In Stage 3 (*fine-tuning*), these curated trajectories are distilled back into the generalist with standard SFT, applicable to both flow-matching and autoregressive heads. We evaluate **PLD** across diverse settings: it achieves a near-saturated 99% task success rate on the LIBERO benchmark, delivers over 50% performance gains in SimplerEnv, and demonstrates a 100% success rate on real-world Franka arm and YAM arm dexterous manipulation tasks. We further provide ablations showing that residual policy probing and distribution-aware replay are key to collecting deployment-aligned data that improves VLAs’ capabilities on both seen and unseen tasks. Our results demonstrate that RL-generated, policy-aligned data can surpass teleoperation-only demonstrations, offering a scalable path toward self-improving VLA models.




Figure 1: We demonstrate the performance of **PLD** on several real-world challenging manipulation tasks. The robot successfully picks up diverse objects and conduct peg insertion for Franka arm. Besides, we also deploy **PLD** on YAM bi-manual settings, showing **PLD** policy continuously perform a continuous 1-hour cycle of GPU insertion and unplugging *without human resets*. (Videos at <https://wenlixiao.com/self-improve-VLA-PLD>)




Figure 2: **Synergetic effect of PLD data.** We fine-tune π_0 on subsets of LIBERO-90 with varying **task coverage ratios**, where each ratio (10–80%) indicates the fraction of distinct task instances included in training relative to the full 90-task distribution. For each ratio, we randomly sample 4 disjoint subsets of tasks and report the averaged results. The x-axis thus represents the degree of task coverage (not the number of trajectories), while the evaluation is always conducted on all 90 tasks. We compare different data formulations: **PLD** data yields the highest in-distribution performance while retaining the cross-task generalization property of high-quality human data. It further enables modest-level zero-shot transfer even when trained on only 10% of tasks (24.4% SR on unseen tasks), whereas the VLA fine-tuned on base-policy rollout data (0-1 REINFORCE) underperforms and fails to generalize. (Success rate numbers are reported in Table 3.)

1 INTRODUCTION

Supervised fine-tuning (SFT) has become the standard post-training paradigm for large language models (LLMs): after broad pre-training, models are adapted to downstream applications by training on curated instruction–response pairs, yielding many improvements in language following, safety, and generalization (Ouyang et al., 2022; Anil et al., 2025). Inspired by these successes, the same recipe is now being applied to robot foundation models, particularly vision-language-action (VLA) policies, where large, heterogeneous robotics and vision-language datasets provide the base initialization, and SFT specializes models to specific tasks and embodiments (O’Neill et al., 2024; Ghosh et al., 2024; Kim et al., 2024; 2025; Black et al., 2024; Bjorck et al., 2025). However, transferring this paradigm from language to robotics is a unique challenge. Collecting high-quality robot demonstrations is both costly and labor-intensive, making large-scale datasets much harder to obtain. Even when such data are available, they are often collected through teleoperation pipelines that are *decoupled* from the deployed VLA policy, leaving critical coverage gaps: human operators must manually anticipate and correct failure modes, but their demonstrations rarely reflect the actual distribution of states the policy will encounter at deployment. As a result, while SFT reliably improves performance on the tasks it is trained on, much less is understood about whether these gains transfer to new tasks and environments.

These challenges raise the following question: Can VLA models improve themselves using RL-curated data with minimal human effort? Specifically, can this self-curated training match or surpass fine-tuning on human-expert (oracle) teleoperation data, both in-distribution and out-of-distribution? Our central observation is that data collection should *not* be agnostic to the base policy: the data-collecting policy and the generalist must *interact*, so that exploration leverages the generalist’s prior knowledge and collected data remain aligned with its trajectory distribution. A natural way to in-

stantiate this idea is to employ reinforcement learning (RL) to acquire task-specific specialists that guide data collection. However, applying RL in this setting is hindered by two key challenges. Sparse reward signals in language-conditioned manipulation tasks render RL unstable and sample-inefficient. Moreover, training task-specific experts independently from the generalist introduces distributional mismatch, and once these experts converge, their behavior often lacks the diversity needed to provide robust coverage for SFT.

Motivated by these challenges, we introduce **PLD**, a three-stage post-training pipeline. **Stage 1: Online specialist acquisition.** We *freeze* the VLA backbone and train several lightweight *residual* actors for multiple tasks via sample-efficient off-policy RL, enabling them to “take over” the base policy at arbitrary states and achieve above 99% task success. **Stage 2: Automatic data collection.** We propose a hybrid rollout scheme that biases residual takeovers toward states frequently visited by the base model, mitigating distribution shift while capturing recovery behaviors. **Stage 3: Supervised fine-tuning.** The collected data for multiple tasks are distilled back into the base model through SFT, a process agnostic to VLA architectures, supporting both flow-matching and autoregressive action heads (Black et al., 2024; Kim et al., 2024). An overview of our pipeline can be found in Figure 3. With **PLD**, we can efficiently acquire task-specific RL experts through VLA-guided exploration. Consequently, the VLA further improves using the **PLD** data, achieving performance above 99% on the LIBERO benchmark.

This paper makes the following contributions: 1) Autonomous post-training recipe. We propose a post-training pipeline that enables VLA models to improve autonomously without relying on additional oracle demonstrations. Our method achieves near-saturated 99% success rates on the LIBERO benchmark, and delivers over 50% performance gains in SimplerEnv, underscoring both its effectiveness on seen tasks and its ability to generalize to unseen ones. 2) Systematic study of RL-generated data. We analyze the key components of automatic data collection most beneficial for SFT, and conduct extensive experiments in simulation and on real robot hardware to examine how *RL-generated data* influences generalization to unseen tasks. 3) Comprehensive empirical validation. We provide large-scale ablations of our design choices. Besides, we showcase >99% success rate on Franka arm and YAM arm dexterous manipulation tasks. Achieving continuous GPU insertion and unplugging operating for 1 hour without human intervention, offering potential for data-efficient post-training of robot foundation models.

2 PRELIMINARIES

2.1 TASK FORMULATION

We study language-conditioned manipulation with *sparse binary rewards* using *Vision–Language–Action* (VLA) models as the base policy class. We assume a partially observed control process with horizon T , where an episode terminates and resets on task success with a restricted time limit. After each episode, a reward $r \in \{0, 1\}$ is assigned. Let g denote the language prompt of goal specification, and let o_t denote partial observations comprising robot proprioception (e.g., joint angle) and RGB images input. The policy consumes (o_t, g) and outputs a 7-DoF action (6-DoF delta pose and 1-DoF continuous gripper command), which we express as $a_t = D_\phi(h_\theta(o_t, g))$, where h_θ is a vision–language backbone and D_ϕ is an action head. Consistent with recent VLA models, D_ϕ is instantiated by one of three common families: (i) a *diffusion* or *flow-based* action head for continuous control (Ghosh et al., 2024; Black et al., 2024), or (ii) a *discrete action tokenizer* for autoregressive decoding (Kim et al., 2024; Pertsch et al., 2025). We aim to maximize success rate $\bar{\Sigma}r$ by tuning ϕ and θ .

2.2 SUPERVISED FINE-TUNING

Given a VLA policy and a demonstration dataset $\mathcal{D} = \{(o_t, g_t, a_t)\}$ of observations o_t , goal specifications g_t , and expert actions a_t , SFT adapts the policy by maximizing the conditional action likelihood. Letting $x_t = (o_t, g_t)$, the canonical objective is the behavior cloning (BC) loss. In contemporary VLA systems, the loss instantiation depends on the action head architecture. Autoregressive/token heads (Kim et al., 2024; Pertsch et al., 2025) train with sequence NLL over action tokens $u_{1:K}$:

$$\mathcal{L}_{\text{AR}}(\theta) = -\mathbb{E}_{k \sim [K]} [\log p_\theta(u_k | u_{<k}, x)],$$




Figure 3: **An overview of PLD.** Our pipeline consists of three stages: 1) learning specialist residual policy for each task via online off-policy RL, with efficient exploration guided by a frozen VLA generalist; 2) Automatic generation of hybrid trajectories by having the VLA rollout for the first t steps and let the specialist takeover to generate recovery data; 3) Supervised fine-tuning using collected multi-task PLD data; 4) Deploy the fine-tuned generalist to diverse manipulation tasks in zero-shot.

With recent work improving efficiency via action chunking and parallel decoding, and a continuous action parameterization trained by an ℓ_1 regression objective (Kim et al., 2025). Diffusion heads model a conditional denoising process for actions and train via score-matching MSE:

$$\mathcal{L}_{\text{diff}}(\theta) = \mathbb{E}_{t, \epsilon, (x, a)} \left[\left\| \epsilon - \epsilon_{\theta}(a_t^{(\text{noisy})}, x, t) \right\|_2^2 \right],$$

enabling iterative sampling at inference (Ghosh et al., 2024; Chi et al., 2024). Flow-matching heads learn a continuous velocity field to transport a prior to the action distribution, trained with an L_2 flow-matching loss, and are often paired with VLM backbones for semantically grounded control (Black et al., 2024; 2025). Across these heads, SFT remains the standard mechanism to specialize a generalist policies to new embodiments and tasks using modest labeled robot data (Kim et al., 2024; 2025).

2.3 GOAL-CONDITIONED RL

We model continuous control as an MDP (Bellman, 1957) $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \rho, \rho_0, r, \gamma)$ with state space \mathcal{S} , action space \mathcal{A} , transition dynamics $\rho(s' | s, a)$, initial-state distribution ρ_0 , reward function r , and discount $\gamma \in (0, 1]$. In *goal-conditioned* settings, each task is specified by a goal variable $g \in \mathcal{G}$ drawn from $p(g)$; the reward becomes goal-dependent $r : \mathcal{S} \times \mathcal{A} \times \mathcal{G} \rightarrow \mathbb{R}$, and the policy is $\pi : \mathcal{S} \times \mathcal{G} \rightarrow \Delta(\mathcal{A})$, written $\pi(a | s, g)$. It is convenient to view GCRL as an augmented MDP on $\mathcal{S} \times \mathcal{G}$ with stationary goals:

$$\tilde{\rho}((s', g) | (s, g), a) = \rho(s' | s, a) \cdot \mathbf{1}\{g' = g\}.$$

Under the infinite-horizon setting, the RL objective is

$$J(\pi) = \mathbb{E}_{g \sim p(g)} \mathbb{E}_{s_0 \sim \rho_0, a_t \sim \pi(\cdot | s_t, g), s_{t+1} \sim \rho(\cdot | s_t, a_t)} \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t, g) \right]. \quad (1)$$

In this paper, we consider a sparse binary reward setting, i.e., $r(s, a, g) = \mathbf{1}[d(\phi(s), g) \leq \varepsilon]$ defined via a success predicate over a goal-relevant representation $\phi(s)$, a metric d , and tolerance $\varepsilon > 0$.

3 METHODS

Method Overview We study the synergy between data produced by our method when a modest *generalist* VLA serves as the policy prior. The premise is that, if we exploit the base policy’s prior

correctly, it can both *solve hard tasks quickly* and *explore efficiently*. While recent work explores direct RL fine-tuning of large VLA (Mark et al., 2024; Dong et al., 2025b), such formulas can be resource-intensive even for single-task tuning: e.g., OpenVLA-OFT requires per-GPU memory up to ~ 62.5 GB for LIBERO training at a batch size of 8 (Kim et al., 2025). Meanwhile, it remains unclear whether these approaches scale gracefully to multi-task fine-tuning under heterogeneous setups. We therefore opt for a *decoupled* pipeline. We freeze the base policy π_b and learn a lightweight residual action policy π_δ with sample-efficient off-policy RL (Gaussian policy parameterization). We then *collect expert data* by letting the residual “take over” after specified steps of “base policy probing”. Finally, we *distill* these skills back into the base model via SFT and deploy the generalist on diverse manipulation tasks. We provide the overview of **PLD** in Figure 3.

3.1 DATA EFFICIENT RL VIA POLICY PRIOR WARM-START

Building upon the previous success of sample-efficient RL with prior data (Ball et al., 2023), we consider an off-policy actor-critic framework and maintain two separate buffers for offline and online experience replay. We first fill the offline buffer with successful rollouts $\mathcal{B}_{offline} = \{\tau_1, \tau_2, \dots\}$ from the base policy π_b . This process serves as an importance sampling to preserve only the successful attempts. During training, the offline and online experiences will be replayed symmetrically; for example, mini-batches consist of equal samples from both buffers, ensuring that the value function is constantly trained on high-value state-action pairs.

In practice, we train a task-specific residual action module $\pi_\delta(\cdot|s, a_b)$ conditioned on $a_b \sim \pi_b$. We use π_δ to explore near the base policy behavior, actively searching for more optimal solutions guided by the Q-function. To modulate exploration and avoid deviating drastically from π_b during the initial phase, the delta action’s magnitude is scaled down to $[-\xi, \xi]$, where $\xi \in [0, 1]$ is tuned by a scheduler. This design choice is two-fold: First, although unable to perfectly generalize to an unseen manipulation task or scenario, the base policy can make reasonable attempts to solve the task, serving as a useful initialization for exploration. Moreover, directly training the expressive foundation policy (e.g., flow action heads) to maximize the Q-value can be extremely difficult (Mark et al., 2024). In contrast, a residual Gaussian policy can be easily trained through any off-the-shelf off-policy RL algorithm.

Alongside π_δ , action value function $Q^{\bar{\pi}}$ acquired through policy iteration and TD-learning (Sutton & Barto, 2018) as in Equation (2), where $\bar{\pi}(\cdot|s)$ is the combined policy.

$$Q^{\bar{\pi}}(s_t, \bar{a}_t) \leftarrow r(s, a) + \gamma \mathbb{E}_{s_{t+1} \sim p(\cdot|s_t, \bar{a}_t)} [Q_{target}^{\bar{\pi}}(s_{t+1}, \bar{a}_{t+1})], \bar{a} = a_b + a_\delta \quad (2)$$

To stabilize off-policy learning and mitigate forgetting, we introduce a warm-up stage using solely π_b for data collection akin to (Zhou et al., 2024b). Meanwhile, the Q-function is initialized by a conservative objective such as Cal-QL (Nakamoto et al., 2024). Importantly, we do not explicitly enforce behavior constraints to policy loss, such that the resulting expert $\bar{\pi}$ is less influenced by either data quality or base policy performance.

3.2 BOOTSTRAPPING RL SPECIALIST FOR SCALABLE DATA GENERATION

We then turn to the question of how to collect demonstration data using RL specialists. Data collected through RL experts is highly optimal, with consistent behavior and nearly no hesitation, demonstrating smooth solutions that finish tasks with a shorter horizon. However, such a narrow distribution of unimodal expert behavior may leave out-of-distribution and failure states underrepresented. Thus, scaling purely expert data may not result in a performance gain, but instead risks the generalist overfitting on these data and harming both robustness and generalization (As discussed in the following section).

To mitigate this issue, we propose a hybrid data collection scheme that incorporates base-policy initialization: We first rollout the base policy for random steps, then let the learned residual RL policy to take over, resulting in demonstration trajectories $\tau_{demo} = \{(s_1, a_{b,1}), \dots, (s_{t-1}, a_{b,t-1})\} \cup \{(s_t, a_{b,t} + \bar{a}_t), \dots\}$ that contain the behavior of the expert recovering from a potential suboptimal region. We refer to this procedure as **base policy probing**. Accordingly, we boost the robustness of the RL expert by training the RL expert on an initial state distribution $s_0 \sim p_0^{\bar{\pi}_b}$ given by random steps of base policy probing. The probing step only serves as state initialization and will not be added to the replay buffer. The details of **PLD** are summarized in Algorithm 1.




Figure 4: **Visualization of Data diversity.** We visualize **PLD** data with different base policy initialization probing horizons. Increasing probing horizon yields longer episodes and greater diversity among successful trials. This broader data support leads to improved fine-tuning performance, which eventually saturates.

4 EXPERIMENTS

In this section, we systematically evaluate **PLD**. We first demonstrate the efficiency of **PLD**-RL in solving sparse-reward manipulation tasks, which serves as the cornerstone of our pipeline. Then we focus on study 1) How does the probing mechanism of **PLD** benefit VLA SFT; 2) How does **PLD** data compare with other sources of demonstrations (e.g., human data, RL expert rollout, VLA base policy rollout). Finally, we investigate the key factors of our pipeline and how they contribute to improving the performance of VLA.

We consider simulation as a proxy to real-world performance, and evaluate methods across two widely adopted simulation benchmarks, including **LIBERO** (Liu et al., 2023), **SimplerEnv** (Li et al., 2024). **LIBERO** is a lifelong learning benchmark focused on language-guided manipulation tasks. It comprises 130 language-conditioned manipulation tasks grouped into four suites that stress object distribution, spatial arrangement, task goals, and their mixture. **SimplerEnv** is a robotics manipulation benchmark that aims for high sim-to-real correlation.

In the following sections, we analyze different data sources: **PLD** data \mathcal{D}^{PLD} , Human data $\mathcal{D}^{\text{Human}}$, RL expert data (RL expert rollout w/o base policy probing) \mathcal{D}^{RL} , and base-policy rollout data (Selective successful rollouts, also referred to as "self-bootstrap data") $\mathcal{D}^{\text{Base Policy}}$. Unless stated otherwise, all methods use identical data volume, training budgets, augmentation, and hyperparameters across architectures; the default base policy we used is π_0 (Black et al., 2024).

4.1 EFFECTIVENESS AND EFFICIENCY OF LEARNING RL SPECIALIST

In this section, we seek answers to the following questions: Does **PLD** benefit from both policy guidance and hybrid online learning? We compare state-of-the-art methods that leverage policy priors and data priors: **WSRL** (Zhou et al., 2024b) (offline initialization only); **RLPD** (Ball et al., 2023) (No base policy guidance). For the pre-training stage, we collect a dataset of 50 trajectories per task, containing only the successful trials of the same base policy (π_0), and using Cal-QL (Nakamoto et al., 2024) as the default pre-training algorithm. Subsequently, we retain these data for methods with online hybrid data replay. We plot the training curve of 250k steps of online interaction, showing mean rollout performance and 95% CIs (confidence level) across 3 seeds in Figure 5.

PLD outperforms baseline methods by a large margin across 8 tasks on **LIBERO-90**, indicating that **PLD** effectively exploits the VLA policy prior and yields pronounced sample efficiency at low interaction budgets. In terms of asymptotic performance, **PLD** can achieve *over 95% performance* on every task that we report to fine-tune performance (over 120 manipulation tasks). Notably, we observe an initial performance drop for **PLD**. This phenomenon implies the initial phase of exploration, where the residual policy starts to diverge from the base policy and visits potentially suboptimal states. Ablation study on **PLD**-RL’s design choice can be found in the Section B.2.




Figure 5: **Benchmarking Sample-Efficient RL Performance.** We compare **PLD** with RL baseline algorithms that either leverage policy prior or data prior. We report mean rollout performance (Average return calculated within a sliding window of 100 episodes) and 95% CIs for 3 seeds across 8 manipulation tasks selected from LIBERO-90.

Table 1: Performance on LIBERO benchmark of VLA models fine-tuned on **PLD** data.

Model	π_0				OpenVLA			
	Spatial	Object	Goal	Avg	Spatial	Object	Goal	Avg
Baseline (SFT/OFT)	95.2	97.6	87.4	93.4	92.9	99.1	83.25	91.8
w/ <i>PLD</i>	97.7	98.5	95.3	97.2	99.5	99.1	98.9	99.2
Δ	+2.5	+0.9	+7.9	+3.8	+6.6	+0.0	+15.7	+7.4

4.2 IN-DISTRIBUTION PERFORMANCE

In this section, we investigate how effectively the proposed pipeline enhances the performance of the VLA. We evaluate in-distribution fine-tuning on the LIBERO benchmark using three subsets, each consisting of 10 language-conditioned tasks: *LIBERO-Object*, *LIBERO-Spatial*, and *LIBERO-Goal*. We additionally report results on a custom suite that consists of 4 tasks from *SimplerEnv*. To demonstrate architecture-agnosticism, we instantiate the base VLA with (i) **OpenVLA** (autoregressive action tokens) (Kim et al., 2024) and (ii) π_0 (flow-matching action head) (Black et al., 2024). Since VLA models are mainly trained on real-world datasets that cannot work out of the box on simulation benchmarks, we leverage their official checkpoints for model fine-tuning on each benchmark as the baseline. At test time, each policy is evaluated on *50 episodes per task*, and we report the mean success rate per suite and average over the benchmark. Table 1 and Table 2 list the performance gain achieved by further applying our method. Across all suites and both architectures, **PLD** data yields consistent absolute gains over human-only SFT while requiring *no additional human demonstrations*. We observe that larger **PLD** datasets monotonically improve in-distribution success and that the distilled generalist notably surpasses the average specialist, indicating effective transfer of task-specific competence into the base VLA.




Figure 6: **Short-to-long generalization.** π_0 fine-tuned on LIBERO-90 and one-shot evaluated on LIBERO-10 long horizon tasks.

Table 2: Evaluate **PLD** on SimplerEnv

Model	WidowX Pick Eggplant	WidowX Pick Carrot	Google Open Drawer	Google Coke Can	Avg
Octo-SFT	65.5	43.3	92.5	85.7	71.8
w/ <i>ours</i>	97.8	93.9	99.3	95.5	96.6
Δ	+32.3	+50.6	+6.8	+9.8	+24.9




Figure 7: **Few-shot generalization.** Scaling in-distribution (LIBERO-goal) **PLD** yields better few-shot performance on new tasks (LIBERO-90).

4.3 GENERALIZATION

Generalization to Unseen tasks To study the synergetic effect of **PLD** data, we examine whether **PLD** data improves *zero-shot* performance on unseen tasks in the LIBERO benchmark (Liu et al., 2023). Concretely, we fine-tune π_0 via SFT using data drawn from the disjoint *coverage subsets* of LIBERO-90 in proportions $\{0.1, 0.3, 0.6, 0.8, 1.0\}$; for each coverage level, we randomly sample tasks to form a new subset in distribution and then evaluate all tasks in the suite. We sampled 4 subsets for each coverage level to provide a more unified result. We consider three different data sources: (i) Ours \mathcal{D}^{PLD} , (ii) human expert data \mathcal{D}^{Human} , and (iii) *self-bootstrapping* data $\mathcal{D}^{\pi_0 \text{ rollout}}$ (equal to 0-1 REINFORCE). We visualize the result in Figure 2. Across coverage levels, π_0 fine-tuned on \mathcal{D}^{PLD} attains the strongest in-distribution performance and maintains robust zero-shot transfer to unseen tasks; human data-only SFT achieves approximately a similar level of zero-shot generalization at the same training budget but lags on in-distribution tasks; π_0 self-bootstrapping rollout data underperforms in-distribution and fails to generalize to out-of-distribution tasks.

Generalization to Out-of-domain We study *few-shot generalization* for tasks with different goals, layouts, and backgrounds. We first collect **PLD** data of varying scales set on *source* tasks (LIBERO-Goal) and evaluate the fine-tuning performance on *target* tasks (LIBERO-90). Specifically, the VLA is also fine-tuned on a small number of oracle demos of target tasks. To analyze transfer by skill family, we select tasks from LIBERO-goal and LIBERO-90 that have high semantic correlation to form a set of source/target tasks. We scaled the size of $|\mathcal{D}^{PLD}|$ from 50 to 500 trajectories and compared against \mathcal{D}^{RL} and \mathcal{D}^{BS} under the same data and training budget. As shown in Figure 7, we observe monotonic improvements in SFT performance as the data scales from 50 to 500 trajectories.

Generalize to Long-horizon We assess skill composition ability on LIBERO-100 by fine-tuning the base VLA on LIBERO-90 (source) and evaluating one-shot (give one human demo each) on the held-out LIBERO-10 long-horizon tasks (target). To construct **PLD** data, we first train residual RL specialists independently on each LIBERO-90 task, then aggregate their successful rollouts.

As shown in Figure 6, the fine-tuning of the data **PLD** exceeds the tuning of the data from the baseline policy roll-out (self-bootstrapped), but still falls short of the performance achieved with demonstrations by human experts.




Figure 8: Visualization of failure mode and recovery behavior in the real-world.

4.4 REAL-WORLD PERFORMANCE

We evaluate our approach on a 7-DoF Franka Emika Panda arm in the real world, considering two sets of canonical manipulation tasks: *pick-and-place* and *peg insertion*, illustrated in Figure 1. Unlike prior works (Luo et al., 2025; Zhou et al., 2024b), we do not restrict task randomization, making real-world reinforcement learning particularly challenging. A more detailed experimental setup is provided in Section D.1.

Data collection and policy training. We first collected 200 teleoperated trajectories to perform supervised fine-tuning (SFT) of the base policy π_0 . Using this initialization, we trained π_0 -**PLD** and π_0 -**RPLD** without human interventions. Both policies reached 100% success on the two tasks within 2 hours of training. We then leveraged the learned expert policies to autonomously collect 200 successful demonstrations each, forming datasets \mathcal{D}^{PLD} and $\mathcal{D}^{\text{RPLD}}$, which were subsequently used to further SFT π_0 , yielding $+\mathcal{D}^{\text{PLD}}$, $+\mathcal{D}^{\text{Human}}$, and $+\mathcal{D}^{\text{RPLD}}$.

Performance and failure modes. Across 30 randomized trials per task, all methods achieved perfect success on peg insertion (30/30), demonstrating robust reactive skills. In cube pick-up, however, $+\mathcal{D}^{\text{RPLD}}$ and $+\mathcal{D}^{\text{Human}}$ succeeded in only 16/30 and 10/30 trials, respectively, while $+\mathcal{D}^{\text{PLD}}$ maintained 30/30. Figure 8 illustrates a typical failure: policies trained on $\mathcal{D}^{\text{RPLD}}$ or $\mathcal{D}^{\text{Human}}$ often pushed the cube into the upper-left corner, where the gripper became stuck. By contrast, $+\mathcal{D}^{\text{PLD}}$ was reliably recovered by repositioning the cube before grasping. Distribution analysis confirms that neither human demonstrations nor RL rollouts visited such corner states, whereas **PLD** explicitly probed the base policy and generated diverse trajectories that captured these cases. This explains its robustness and highlights its potential as a self-improving data flywheel. We also consider a more challenging setting of the randomized evaluation environment, demonstrating the generalizability of **PLD** even in the real world. Details can be found in Section D.2.

Robustness for long-horizon tasks. To evaluate the robustness of **PLD** in executing long-horizon and dexterous manipulation tasks, we set up two 6-DoF YAM robot arms developed by I2RT-Robotics (2025). We consider an industrial insertion task—specifically, inserting a micro graphics card into a motherboard. To enable fully autonomous operation without human intervention or re-setting, we decompose the task into four stages: Stage 1: Pick up the GPU from the table and insert it into slot 1. Stage 2: Move the GPU from slot 1 to slot 3. Stage 3: Firmly insert the GPU into slot 3. Stage 4: Unplug the GPU from slot 3 and place it back on the table. A reward classifier is trained to govern the state machine that coordinates these stages. After at most 8 hours of training for each




Figure 9: **Real-world Generalization Performance.** We evaluate one model’s multi-task performance on three language-conditioned manipulation tasks, including pick-and-place and peg insertion.

subtask and distilling the learned skills into a single BC base policy, the system can continuously perform the full task loop without human assistance for at least 1 hour. As shown in the video, although the one-shot success rate for each stage is not 100%, the system is capable of recovering from failures, keeping the data flywheel running autonomously.




Figure 10: **Visualization of different data sources.** We plot 20 trajectories for each method (task prompt: “pick up the black bowl and place it on the plate”). RL expert data is of high quality but lacks diversity and diverges far from base policy behavior, while **PLD** data aligns better with the base policy and contains diverse recovery behavior. (More interactive visualizations at <https://wenlixiao.com/self-improve-VLA-PLD>).

4.5 HOW DOES **PLD** WORK?

We take a deeper look at the underlying reason for **PLD** data’s bonus in generalization. As shown in Figure 10, we plot 50 trajectories for each method (task description: “open middle drawer of the middle cabinet”). RL expert provides optimal and concentrated solutions to the task, but lacks

diversity and diverges far from the behavior of the base policy, while **PLD** data are clustered near the trials of the base policy and contain various recovery behaviors. Based on empirical observation, we hypothesize that due to the base policy probing, **PLD** data provides a solution that is biased towards the base policy, thus fine-tuning forgets less of the base model’s generalizability. This resembles observations in LLM fine-tune (Shenfeld et al., 2025), where the KL-divergence can serve as an indicator of forgetting. Meanwhile, large data coverage also benefits robustness in sequential decision making (Kelly et al., 2019).

In addition, we study sensitivity to the initialization horizon. We choose task 0-9 from LIBERO-90, change the steps we used to initialize the random sample, initiating steps $T_{\text{base}} \sim [0, \alpha T]$ to rollout the base policy. $\alpha \in [0.0, 0.2, 0.4, 0.6, 0.8]$. As α increases, the average episode length of successful trajectories increases, indicating a detour required to correct the suboptimal behavior of the base policy. As demonstrated in Figure 11, performance plateaus at $\alpha = 0.6$ and drops as α increases further. This is consistent with our analysis that SFT benefits from the data diversity.




Figure 11: **Ablation of Probing Horizon.** Performance plateau at $\alpha = 0.6$.

5 RELATED WORK

5.1 ROBOTICS FOUNDATION MODELS

Following the success of large language models and vision language models (Brown et al., 2020; Touvron et al., 2023; Chen et al., 2022), recent works on robotics foundation models turned to a similar transformer-based architecture with aggressive data scaling. This inspired earlier works in VLAs such as RT-1, RT-2, and OpenVLA, etc. (Brohan et al., 2023b;a; Kim et al., 2024; Xue et al., 2025). Meanwhile, diffusion-based action generation, explored in Chi et al. (2024), takes motivation from generative modeling techniques (Ho et al., 2020), demonstrating smooth and accurate action generation. This has led to more recent VLA architectures to-date, such as Octo (Ghosh et al., 2024), OpenVLA-OFT (Kim et al., 2025), GR00T (Bjorck et al., 2025), and the π -series of models (Black et al., 2024; 2025; Pertsch et al., 2025). The VLA training procedure is typically analogous to VLM training. First, model weights are initialized from the respective VLM backbones (Kim et al., 2024; Black et al., 2024). Then, the model is supervised with next-token-prediction tasks on diverse pretraining datasets, spanning across multi-modal web data (Black et al., 2025) such as COCO (Chen et al., 2015) and VQA_{v2} (Goyal et al., 2017), and robotics-specific, cross-embodiment data (Khazatsky et al., 2025; O’Neill et al., 2024). Finally, supervised fine-tuning is conducted on a small set of high-quality teleoperation data collected from the target robot deployment platform performing the target tasks.

5.2 SAMPLE-EFFICIENT RL WITH DATA AND POLICY PRIORS

Sample and exploration efficiency have been a long-standing problem in RL, especially in sparse-reward settings. Recent works have explored leveraging offline data to improve sample efficiency. Offline-to-online transfer (Vecerik et al., 2017; Nair et al., 2020; Kostrikov et al., 2021; Nakamoto et al., 2024; Zhou et al., 2024b; Li et al., 2025) considers a two-stage pipeline that first initializes policy or critic using pessimism or constrained objective in offline RL (Levine et al., 2020) and follows with an online fine-tuning phase to have new data collected and alleviate distributional shift; Hybrid RL (Song et al., 2022; 2024; Ball et al., 2023) considers online RL with access to an offline dataset. Given expert demonstration, one can either continuously replay this data to ensure high-value state visitation (Ball et al., 2023) or to guide exploration (Dong et al., 2025a). Data prior can also guide reset-free real-world learning (Walke et al., 2023; Sharma et al., 2023). Another line of work assumes access to policy prior, such as a pre-trained generalist. Ye et al. (2023); Chen et al. (2025); Jülg et al. (2025) leverage foundation policy to guide RL through an auxiliary behavior regularization objective. Action editing is another efficient way to improve upon the policy prior. ResiP (Ankile et al., 2025) considers learning a residual policy through PPO (Schulman et al., 2017), while EXPO (Dong et al., 2025b) considers an off-policy solution and co-trains the base policy during the process. Our work leverages a suboptimal base policy to achieve a non-zero success rate

for warm-starting exploration, but does not require access to oracle demos or a human expert for further intervention.

5.3 VLA POST-TRAINING

The prevailing large-scale recipe for VLA post-training is to *pretrain* on diverse, heterogeneous robot data and then *fine-tune* on task-specific demonstrations (Zhou et al., 2024a; Black et al., 2024). For example, Black et al. (2024) performs supervised post-training on a carefully curated task-targeted corpus, with per-task coverage ranging from a few to over 100 hours of teleoperation. Because such post-training data are expensive to acquire, the authors note that most diversity must come from the pretraining mixture—underscoring a key limitation of pure SFT: data scarcity and limited coverage at adaptation time. To enable self-improvement, prior work has explored scaling high-quality data via *online RL specialists* (Ball et al., 2023). However, these pipelines often require substantial human intervention and collect data in a large way *agnostic* to the generalist’s behavior, restricting scalability. Other lines investigate *on-policy* RL for post-training (Lu et al., 2025; Tan et al., 2025), or optimize *single-task* fine-tuning at the expense of generalization (Chen et al., 2025). Our work jointly targets these limitations by seeking a post-training pipeline that reduces human effort, aligns data collection with the generalist’s state distribution, and remains sufficiently sample efficient for real-world systems.

6 CONCLUSIONS

We presented **PLD**, a three-stage post-training pipeline that enables VLA models to improve autonomously without relying on additional oracle human demonstrations. **PLD** couples a frozen VLA generalist with lightweight *residual* RL specialists to warm-start exploration and distills curated successes back into the base model with standard SFT. Across large-scale simulation experiments and real-world deployment, **PLD** improves without additional human demonstration, achieving near-saturated $\sim 99\%$ success on LIBERO, $>50\%$ gains in SimplerEnv, and robust real-world performance. Ablations identify *residual policy probing* and *distribution-aware replay* as key to stability, sample efficiency, and generalization. We consider **PLD** as a practical step toward autonomous, scalable post-training and a foundation for future work on multi-embodiment transfer, continual on-robot learning, and safety-constrained data collection.

7 ACKNOWLEDGMENTS

We are grateful to Jason Liu, Tony Tao, Colin Li, Max Fu, Yuhui Chen, Ajay Mandlekar, You Liang Tan, Dennis Da, Haoyu Xiong, Stephanie Chen, Charles Xu, and Guanzhi Wang for their insightful discussions and technical support. We also thank Tri Cao, Jeremy Chimienti, and Lion Park for their assistance with data collection and mechanical setup. Finally, we thank the GEAR Team and LeCAR Lab for their continuous support.

REFERENCES

- Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M. Dai, Anja Hauth, Katie Millican, David Silver, Melvin Johnson, Ioannis Antonoglou, Julian Schrittwieser, Amelia Glaese, Jilin Chen, Emily Pitler, Timothy Lillicrap, Angeliki Lazaridou, Orhan Firat, James Molloy, Michael Isard, Paul R. Barham, Tom Hennigan, Benjamin Lee, Fabio Viola, Malcolm Reynolds, Yuanzhong Xu, Ryan Doherty, et al. Gemini: A family of highly capable multimodal models, 2025. URL <https://arxiv.org/abs/2312.11805>.
- Lars Ankile, Anthony Simeonov, Idan Shenfeld, Marcel Torne, and Pulkit Agrawal. From imitation to refinement-residual rl for precise assembly. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 01–08. IEEE, 2025.
- Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

- Philip J Ball, Laura Smith, Ilya Kostrikov, and Sergey Levine. Efficient online reinforcement learning with offline data. In *International Conference on Machine Learning*, pp. 1577–1594. PMLR, 2023.
- Richard Bellman. A markovian decision process. *Journal of mathematics and mechanics*, pp. 679–684, 1957.
- Johan Bjorck, Fernando Castañeda, Nikita Cherniadev, Xingye Da, Runyu Ding, Linxi Fan, Yu Fang, Dieter Fox, Fengyuan Hu, Spencer Huang, et al. Gr00t n1: An open foundation model for generalist humanoid robots. *arXiv preprint arXiv:2503.14734*, 2025.
- Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, et al. π_0 : A vision-language-action flow model for general robot control. *arXiv preprint arXiv:2410.24164*, 2024.
- Kevin Black, Noah Brown, James Darpanian, Karan Dhabalia, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Manuel Y. Galliker, Dibya Ghosh, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Devin LeBlanc, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Allen Z. Ren, Lucy Xiaoyang Shi, Laura Smith, Jost Tobias Springenberg, Kyle Stachowicz, James Tanner, Quan Vuong, Homer Walke, Anna Walling, Haohuan Wang, Lili Yu, and Ury Zhilinsky. $\pi_{0.5}$: a vision-language-action model with open-world generalization. *arXiv preprint arXiv:2504.16054*, 2025.
- Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Xi Chen, Krzysztof Choromanski, Tianli Ding, Danny Driess, Avinava Dubey, Chelsea Finn, Pete Florence, Chuyuan Fu, Montse Gonzalez Arenas, Keerthana Gopalakrishnan, Kehang Han, Karol Hausman, Alexander Herzog, Jasmine Hsu, Brian Ichter, Alex Irpan, Nikhil Joshi, Ryan Julian, Dmitry Kalashnikov, Yuheng Kuang, Isabel Leal, Lisa Lee, Tsang-Wei Edward Lee, Sergey Levine, Yao Lu, Henryk Michalewski, Igor Mordatch, Karl Pertsch, Kanishka Rao, Krista Reymann, Michael Ryoo, Grecia Salazar, Pannag Sanketi, Pierre Sermanet, Jaspiar Singh, Anikait Singh, Radu Soricut, Huong Tran, Vincent Vanhoucke, Quan Vuong, Ayzaan Wahid, Stefan Welker, Paul Wohlhart, Jialin Wu, Fei Xia, Ted Xiao, Peng Xu, Sichun Xu, Tianhe Yu, and Brianna Zitkovich. Rt-2: Vision-language-action models transfer web knowledge to robotic control, 2023a. URL <https://arxiv.org/abs/2307.15818>.
- Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Joseph Dabis, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, Jasmine Hsu, Julian Ibarz, Brian Ichter, Alex Irpan, Tomas Jackson, Sally Jesmonth, Nikhil J Joshi, Ryan Julian, Dmitry Kalashnikov, Yuheng Kuang, Isabel Leal, Kuang-Huei Lee, Sergey Levine, Yao Lu, Utsav Malla, Deeksha Manjunath, Igor Mordatch, Ofir Nachum, Carolina Parada, Jodilyn Peralta, Emily Perez, Karl Pertsch, Jornell Quiambao, Kanishka Rao, Michael Ryoo, Grecia Salazar, Pannag Sanketi, Kevin Sayed, Jaspiar Singh, Sumedh Sontakke, Austin Stone, Clayton Tan, Huong Tran, Vincent Vanhoucke, Steve Vega, Quan Vuong, Fei Xia, Ted Xiao, Peng Xu, Sichun Xu, Tianhe Yu, and Brianna Zitkovich. Rt-1: Robotics transformer for real-world control at scale, 2023b. URL <https://arxiv.org/abs/2212.06817>.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/1457c0d6bfc4967418bf8ac142f64a-Paper.pdf.
- Xi Chen, Xiao Wang, Soravit Changpinyo, Piotr Padlewski, Daniel Salz, Sebastian Goodman, Adam Grycner, Basil Mustafa, Lucas Beyer, et al. Pali: A jointly-scaled multilingual language-image model. *arXiv preprint arXiv:2209.06794*, 2022.

- Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollar, and C. Lawrence Zitnick. Microsoft coco captions: Data collection and evaluation server, 2015. URL <https://arxiv.org/abs/1504.00325>.
- Yuhui Chen, Shuai Tian, Shugao Liu, Yingting Zhou, Haoran Li, and Dongbin Zhao. Confrt: A reinforced fine-tuning method for vla models via consistency policy. *arXiv preprint arXiv:2502.05450*, 2025.
- Cheng Chi, Zhenjia Xu, Siyuan Feng, Eric Cousineau, Yilun Du, Benjamin Burchfiel, Russ Tedrake, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion, 2024. URL <https://arxiv.org/abs/2303.04137>.
- Perry Dong, Alec M Lessing, Annie S Chen, and Chelsea Finn. Reinforcement learning via implicit imitation guidance. *arXiv preprint arXiv:2506.07505*, 2025a.
- Perry Dong, Qiyang Li, Dorsa Sadigh, and Chelsea Finn. Expo: Stable reinforcement learning with expressive policies. *arXiv preprint arXiv:2507.07986*, 2025b.
- Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.
- Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International conference on machine learning*, pp. 1587–1596. PMLR, 2018.
- Dibya Ghosh, Homer Walke, Karl Pertsch, Kevin Black, Oier Mees, Sudeep Dasari, Joey Hejna, Tobias Kreiman, Charles Xu, et al. Octo: An open-source generalist robot policy. *arXiv preprint arXiv:2405.12213*, 2024.
- Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6904–6913, 2017.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models, 2020. URL <https://arxiv.org/abs/2006.11239>.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL <https://arxiv.org/abs/2106.09685>.
- I2RT-Robotics. Yam – 6-dof robotic arm. <https://i2rt.com/products/yam-manipulator>, 2025.
- Tobias Jülg, Wolfram Burgard, and Florian Walter. Refined policy distillation: From vla generalists to rl experts. *arXiv preprint arXiv:2503.05833*, 2025.
- Michael Kelly, Chelsea Sidrane, Katherine Driggs-Campbell, and Mykel J Kochenderfer. Hgdagger: Interactive imitation learning with human experts. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 8077–8083. IEEE, 2019.
- Alexander Khazatsky, Karl Pertsch, Suraj Nair, Ashwin Balakrishna, Sudeep Dasari, Siddharth Karamcheti, Soroush Nasiriany, Mohan Kumar Srirama, Lawrence Yunliang Chen, Kirsty Ellis, Peter David Fagan, Joey Hejna, Masha Itkina, Marion Lepert, Yecheng Jason Ma, Patrick Tree Miller, Jimmy Wu, Suneel Belkhale, Shivin Dass, Huy Ha, Arhan Jain, Abraham Lee, Youngwoon Lee, Marius Memmel, Sungjae Park, Ilija Radosavovic, Kaiyuan Wang, Albert Zhan, Kevin Black, Cheng Chi, Kyle Beltran Hatch, Shan Lin, Jingpei Lu, Jean Mercat, Abdul Rehman, Pannag R Sanketi, Archit Sharma, Cody Simpson, Quan Vuong, Homer Rich Walke, Blake Wulfe, Ted Xiao, Jonathan Heewon Yang, Arefeh Yavary, Tony Z. Zhao, Christopher Agia, Rohan Baijal, Mateo Guaman Castro, Daphne Chen, Qiuyu Chen, Trinity Chung, Jaimyn Drake, Ethan Paul Foster, Jensen Gao, Vitor Guizilini, David Antonio Herrera, Minh Heo, Kyle Hsu, Jiaheng Hu, Muhammad Zubair Irshad, Donovan Jackson, Charlotte Le, Yunshuang Li, Kevin Lin, Roy Lin, Zehan Ma, Abhiram Maddukuri, Suvir Mirchandani, Daniel Morton, Tony Nguyen, Abigail O’Neill, Rosario Scalise, Derick Seale, Victor Son, Stephen Tian, Emi Tran, Andrew E. Wang, Yilin Wu, Annie Xie, Jingyun Yang, Patrick Yin, Yunchu Zhang, Osbert Bastani,

- Glen Berseth, Jeannette Bohg, Ken Goldberg, Abhinav Gupta, Abhishek Gupta, Dinesh Jayaraman, Joseph J Lim, Jitendra Malik, Roberto Martín-Martín, Subramanian Ramamoorthy, Dorsa Sadigh, Shuran Song, Jiajun Wu, Michael C. Yip, Yuke Zhu, Thomas Kollar, Sergey Levine, and Chelsea Finn. Droid: A large-scale in-the-wild robot manipulation dataset, 2025. URL <https://arxiv.org/abs/2403.12945>.
- Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, et al. Openvla: An open-source vision-language-action model. *arXiv preprint arXiv:2406.09246*, 2024.
- Moo Jin Kim, Chelsea Finn, and Percy Liang. Fine-tuning vision-language-action models: Optimizing speed and success. *arXiv preprint arXiv:2502.19645*, 2025.
- Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. *arXiv preprint arXiv:2110.06169*, 2021.
- Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *Advances in neural information processing systems*, 33:1179–1191, 2020.
- Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.
- Qiyang Li, Zhiyuan Zhou, and Sergey Levine. Reinforcement learning with action chunking. *arXiv preprint arXiv:2507.07969*, 2025.
- Xuanlin Li, Kyle Hsu, Jiayuan Gu, Karl Pertsch, Oier Mees, Homer Rich Walke, Chuyuan Fu, Ishikaa Lunawat, Isabel Sieh, Sean Kirmani, et al. Evaluating real-world robot manipulation policies in simulation. *arXiv preprint arXiv:2405.05941*, 2024.
- Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.
- Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. Libero: Benchmarking knowledge transfer for lifelong robot learning. *Advances in Neural Information Processing Systems*, 36:44776–44791, 2023.
- Guanxing Lu, Wenkai Guo, Chubin Zhang, Yuheng Zhou, Haonan Jiang, Zifeng Gao, Yansong Tang, and Ziwei Wang. Vla-rl: Towards masterful and general robotic manipulation with scalable reinforcement learning. *arXiv preprint arXiv:2505.18719*, 2025.
- Jianlan Luo, Zheyuan Hu, Charles Xu, You Liang Tan, Jacob Berg, Archit Sharma, Stefan Schaal, Chelsea Finn, Abhishek Gupta, and Sergey Levine. Serl: A software suite for sample-efficient robotic reinforcement learning. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 16961–16969. IEEE, 2024.
- Jianlan Luo, Charles Xu, Jeffrey Wu, and Sergey Levine. Precise and dexterous robotic manipulation via human-in-the-loop reinforcement learning. *Science Robotics*, 10(105):eads5033, 2025.
- Max Sobol Mark, Tian Gao, Georgia Gabriela Sampaio, Mohan Kumar Srirama, Archit Sharma, Chelsea Finn, and Aviral Kumar. Policy agnostic rl: Offline rl and online rl fine-tuning of any class and backbone. *arXiv preprint arXiv:2412.06685*, 2024.
- Ashvin Nair, Abhishek Gupta, Murtaza Dalal, and Sergey Levine. Awac: Accelerating online reinforcement learning with offline datasets. *arXiv preprint arXiv:2006.09359*, 2020.
- Mitsuhiko Nakamoto, Simon Zhai, Anikait Singh, Max Sobol Mark, Yi Ma, Chelsea Finn, Aviral Kumar, and Sergey Levine. Cal-ql: Calibrated offline rl pre-training for efficient online fine-tuning. *Advances in Neural Information Processing Systems*, 36, 2024.
- Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback, 2022. URL <https://arxiv.org/abs/2203.02155>.

- Abby O’Neill, Abdul Rehman, Abhiram Maddukuri, Abhishek Gupta, Abhishek Padalkar, Abraham Lee, Acorn Pooley, Agrim Gupta, Ajay Mandlekar, Ajinkya Jain, et al. Open x-embodiment: Robotic learning datasets and rt-x models: Open x-embodiment collaboration 0. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6892–6903. IEEE, 2024.
- Karl Pertsch, Kyle Stachowicz, Brian Ichter, Danny Driess, Suraj Nair, Quan Vuong, Oier Mees, Chelsea Finn, and Sergey Levine. Fast: Efficient action tokenization for vision-language-action models. *arXiv preprint arXiv:2501.09747*, 2025.
- John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- Archit Sharma, Ahmed M Ahmed, Rehaan Ahmad, and Chelsea Finn. Self-improving robots: End-to-end autonomous visuomotor reinforcement learning. *arXiv preprint arXiv:2303.01488*, 2023.
- Idan Shenfeld, Jyothish Pari, and Pulkit Agrawal. RL’s razor: Why online reinforcement learning forgets less. *arXiv preprint arXiv:2509.04259*, 2025.
- Yuda Song, Yifei Zhou, Ayush Sekhari, J Andrew Bagnell, Akshay Krishnamurthy, and Wen Sun. Hybrid rl: Using both offline and online data can make rl efficient. *arXiv preprint arXiv:2210.06718*, 2022.
- Yuda Song, J Andrew Bagnell, and Aarti Singh. Hybrid reinforcement learning from offline observation alone. *arXiv preprint arXiv:2406.07253*, 2024.
- Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.
- Shuhan Tan, Kairan Dou, Yue Zhao, and Philipp Krähenbühl. Interactive post-training for vision-language-action models. *arXiv preprint arXiv:2505.17016*, 2025.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023. URL <https://arxiv.org/abs/2307.09288>.
- Ikechukwu Uchendu, Ted Xiao, Yao Lu, Banghua Zhu, Mengyuan Yan, Joséphine Simon, Matthew Bennis, Chuyuan Fu, Cong Ma, Jiantao Jiao, et al. Jump-start reinforcement learning. In *International Conference on Machine Learning*, pp. 34556–34583. PMLR, 2023.
- Mel Vecerik, Todd Hester, Jonathan Scholz, Fumin Wang, Olivier Pietquin, Bilal Piot, Nicolas Heess, Thomas Rothörl, Thomas Lampe, and Martin Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *arXiv preprint arXiv:1707.08817*, 2017.
- Homer Rich Walke, Jonathan Heewon Yang, Albert Yu, Aviral Kumar, Jędrzej Orbik, Avi Singh, and Sergey Levine. Don’t start from scratch: Leveraging prior data to automate robotic reinforcement learning. In *Conference on Robot Learning*, pp. 1652–1662. PMLR, 2023.
- Haoru Xue, Xiaoyu Huang, Dantong Niu, Qiayuan Liao, Thomas Kragerud, Jan Tommy Gravdahl, Xue Bin Peng, Guanya Shi, Trevor Darrell, Koushil Sreenath, and Shankar Sastry. Leverb: Humanoid whole-body control with latent vision-language instruction, 2025. URL <https://arxiv.org/abs/2506.13751>.

Weirui Ye, Yunsheng Zhang, Haoyang Weng, Xianfan Gu, Shengjie Wang, Tong Zhang, Mengchen Wang, Pieter Abbeel, and Yang Gao. Reinforcement learning with foundation priors: Let the embodied agent efficiently learn on its own. *arXiv preprint arXiv:2310.02635*, 2023.

Zhiyuan Zhou, Pranav Atreya, Abraham Lee, Homer Walke, Oier Mees, and Sergey Levine. Autonomous improvement of instruction following skills via foundation models. *arXiv preprint arXiv:2407.20635*, 2024a.

Zhiyuan Zhou, Andy Peng, Qiyang Li, Sergey Levine, and Aviral Kumar. Efficient online reinforcement learning fine-tuning need not retain offline data. *arXiv preprint arXiv:2412.07762*, 2024b.

A ALGORITHM

Algorithm 1 PLD with base-policy initialization

Require: $\pi_b, \pi_\delta, Q_\phi, Q_{\phi'}, \alpha, \gamma, \mathcal{B}_{\text{offline}}, \mathcal{B}_{\text{online}}$

Initialization

Collect n successful trials of π_b : $\mathcal{D}_{\text{offline}} = \{\tau_1, \tau_2, \dots, \tau_n\}$

Initialize online buffer $\mathcal{D}_{\text{online}} = \emptyset$

Initialize the critic network $Q_\phi, Q_{\phi'}$ with Cal-QL on $\mathcal{D}_{\text{offline}}$

Randomly initialize delta policy network π_δ

RL training

Freeze π_b , denote $\bar{\pi}(\cdot|s) = \pi_b(\cdot|s)\pi_\delta(\cdot|s, a_b)$

for each RL step **do**

if collect data **then**

if Warm up step **then**

 base model rollout $a \sim \pi_{\text{base}}(\cdot|s)$

else

 sample action $\bar{a} \sim \bar{\pi}(\cdot|s)$

end if

 Environment step: $r, s', done = env.step(\bar{a})$

 Add (s, a, μ, r, s') to buffer $\mathcal{D}_{\text{online}}$.

end if

 Equally sample data from online and offline buffer: $b \sim \mathcal{D}_{\text{online}} \cup \mathcal{D}_{\text{offline}}$

 Calculate TD target by bootstrapping $\bar{\pi}$

 Update Q_ϕ by Equation (2)

 Update π_δ by maximizing the SAC target

Polyak update $\phi' = \rho\phi' + (1 - \rho)\phi$

end for

#Base policy SFT

For each task, we collect hybrid behavior dataset \mathcal{D}_{SFT} :

$$\pi(s_t) = \begin{cases} a_{\text{base}}, & t < T_{\text{base}} \\ a_{\text{base}} + a_\delta, & t \geq T_{\text{base}} \end{cases}$$

for each SFT step **do**

 update π_b by BC objective.

end for

Return π_b

Table 3: LIBERO-90 Success rate for π_0 SFT with different dataset.

PLD Data			Base Policy Rollout Data			Human Data		
Ratio	Overall SR	Seen/Unseen	Ratio	Overall SR	Seen/Unseen	Ratio	Overall SR	Seen/Unseen
0.1	0.314	0.941	0.1	0.103	0.523	0.1	0.272	0.796
		0.244			0.056			0.214
0.3	0.470	0.968	0.3	0.068	0.198	0.3	0.419	0.829
		0.259			0.015			0.240
0.6	0.637	0.872	0.6	0.328	0.506	0.6	0.611	0.829
		0.283			0.062			0.286
0.8	0.745	0.864	0.8	0.344	0.423	0.8	0.694	0.803
		0.268			0.031			0.256
1.0	0.871	0.871	1.0	0.488	0.488	1.0	0.815	0.815
		N/A			N/A			N/A

Table 4: Selected LIBERO-90 Tasks for RL Ablation Studies.

Visualization	Task Name and Description
	<p>LIBERO Task 1 close the top drawer of the cabinet and put the black bowl on top of it</p>
	<p>LIBERO Task 2 put the black bowl in the top drawer of the cabinet</p>
	<p>LIBERO Task 17 stack the middle black bowl on the back black bowl</p>
	<p>LIBERO Task 21 turn on the stove and put the frying pan on it</p>
	<p>LIBERO Task 33 close the microwave</p>
	<p>LIBERO Task 34 put the yellow and white mug to the front of the white mug</p>

continued on next page

continued from previous page

Visualization	Task Name and Description
	LIBERO Task 46 pick up the alphabet soup and put it in the basket
	LIBERO Task 47 pick up the cream cheese box and put it in the basket

B IMPLEMENTATION

B.1 RL BASELINES

To ensure an apple-to-apple comparison in Section 4.1, we implement these baselines based on the SERL Luo et al. (2024) framework and adapt them to fit in the settings of our study. We provide a detailed explanation of baseline formulation and our implementation.

RLPD RLPD (Ball et al., 2023) proposed a hybrid RL pipeline that leverages offline data to foster learning in challenging sparse reward settings. During training, it equally draws samples from both the online and offline buffer. It also uses LayerNorm to deal with the Q-value blow-ups common when querying OOD actions under a high update-to-data (UTD) ratio. We refer to the implementation in the SERL software for both simulation and real deployment.

WSRL In the original paper (Zhou et al., 2024b), WSRL uses Cal-QL (Nakamoto et al., 2024) to pre-train both the action and critic during the offline phase. For the online phase, it discards offline data and warms up the replay buffer with 50k steps of pre-trained policy rollouts. We did not provide a large, diverse dataset like D4RL (Fu et al., 2020) benchmark. Rather, we use the same procedure as PLD to collect successful trajectories from the base model. We implement WSRL under the SERL framework, as the UTD is no longer fixed to 4. This baseline can be considered as an ablation of the residual policy and offline data replay. We use the WSRL baseline as an ablation study of the warm-up online exploration using the base policy, and offline data retention through hybrid data replay.

JSRL Jump-start RL (Uchendu et al., 2023) is a meta-algorithm using an existing guide policy to “rolling-in”. The key mechanism is to shape the initial-state distribution for the learner: JSRL repeatedly resets episodes from states that the guide visits (a curriculum from easy/near-goal states to harder/far-from-goal states), making difficult tasks learnable with fewer trials. It leverages the guide policy for data collection, without directly imitating its actions. JSRL is agnostic to the underlying RL backbone. In practice, we choose SAC to learn the exploration policy. Since JSRL only leverages the policy prior (VLA policy in practice) to warm-up exploration during online interaction, we use it as an ablation of the hybrid experience replay mechanism.

Cal-QL Calibrated Q-learning (Nakamoto et al., 2024) addresses the underestimation issue of CQL (Kumar et al., 2020), thereby significantly improving fine-tuning performance in the offline-to-

online setting. It learns a conservative value function that underestimates the value of OOD actions, while ensuring the values are within a reasonable scale. In practice, it under-bounds the conservative Q function by the value of the behavior policy μ (policy corresponds to the offline dataset \mathcal{D}). The modified Q-learning objective is the following:

$$\min_{\theta} \alpha (\mathbb{E}_{s \sim \mathcal{D}, a \sim \pi} [\max(Q_{\theta}(s, a), V^{\mu}(s))] - \frac{1}{2} \mathbb{E}_{s, a \sim \mathcal{D}} [(Q_{\theta}(s, a) - \mathcal{B}^{\pi} \bar{Q}(s, a))^2],$$

where \bar{Q} is the target Q-value function and the second term corresponds to minimizing TD-error [Lillicrap et al. \(2015\)](#).

Implicit Q-Learning (IQL). IQL is an in-sample offline RL method that avoids querying Q on out-of-distribution actions while still improving over the behavior policy ([Kostrikov et al., 2021](#)). The key step is to fit a *state value* V_{ψ} by *expectile regression* over the actions of the dataset and then bootstrap Q_{θ} toward this value. Let $\delta(s, a) = Q_{\theta}(s, a) - V_{\psi}(s)$ and define the expectile loss $\mathcal{L}_{\eta}(\delta) = |\eta - \mathbf{1}\{\delta < 0\}| \delta^2$ with $\eta \in (0.5, 1)$. IQL alternates

$$(V) \quad \min_{\psi} \mathbb{E}_{(s, a) \sim \mathcal{D}} [\mathcal{L}_{\eta}(Q_{\theta}(s, a) - V_{\psi}(s))], \quad (3)$$

$$(Q) \quad \min_{\theta} \mathbb{E}_{(s, a, s') \sim \mathcal{D}} [(Q_{\theta}(s, a) - (r + \gamma V_{\psi}(s')))^2], \quad (4)$$

$$(\text{policy}) \quad \max_{\phi} \mathbb{E}_{(s, a) \sim \mathcal{D}} \left[\exp\left(\frac{Q_{\theta}(s, a) - V_{\psi}(s)}{\beta}\right) \log \pi_{\phi}(a | s) \right], \quad (5)$$

which realizes policy improvement without out-of-distribution action queries (the policy step reduces to advantage-weighted regression) ([Kostrikov et al., 2021](#)). In our comparison to *Cal-QL* ([Nakamoto et al., 2024](#)) as a critic-initialization baseline, we consider a simplified version of IQL that *directly* regresses Q_{θ} toward an n -step return $R_t = \sum_{i=t}^{t+n-1} \gamma^{i-t} r_i + \gamma^n V_{\psi}(s_{t+n})$ using expectile regression:

$$\min_{\theta} \mathbb{E}_{(s_t, a_t) \sim \mathcal{D}} [\mathcal{L}_{\eta}(Q_{\theta}(s_t, a_t) - R_t)].$$

Unless otherwise noted, we set $\eta = 0.7$, a value shown to propagate high-value signals effectively in the IQL paper.

B.2 DESIGN CHOICES OF **PLD**

In this section, we provide a detailed study of design choices that make **PLD** data efficient and achieve high convergence performance. We evaluate all algorithms on the selected 8 LIBERO-90 tasks.

Reward shaping We empirically analyze the impact of naive reward shaping. Specifically, we consider a step-wise *survival cost* as reward bias as in prior works [Luo et al. \(2024\)](#). As shown in Figure 12, adding a slight reward bias has little impact, but it could increase convergence speed in 2 out of 8 tasks; However, A large bias could significantly hinder performance. For the major results reported in the main paper, we do not apply reward shaping.

Action scale One core component of residential policies is the scale of exploration. To avoid unlearning results from diverging too far from the base policy, delta actions are usually scaled down and bounded within a range of $[-\xi, \xi]$ ([Ankile et al., 2025](#); [Dong et al., 2025b](#)). Figure 13 compares different residual action scales. Setting ξ too large at the start can degrade early performance: updates deviate excessively from the base policy, inducing unstable exploration, while a small ξ will lead to insufficient exploration and lower asymptotic performance. We argue that ξ needs to be carefully tuned to enable exploration while minimizing performance drop. For single-arm manipulation, we suggest $\xi = 0.5$ a good choice for LIBERO and $\xi = 0.1$ for SimplerEnv.

Critic pre-training While warm-start through pre-training the critic is beneficial to asymptotic performance and prevents initial performance drop, the careful selection of the pre-training method could be important as well. We compare using CQL, Cal-QL, and IQL to the pre-training method. We consider using only 50 trajectories of successful trials of the base policy, while the standard offline RL benchmark tends to have far larger data volume ([Fu et al., 2020](#)). In Figure 14, online




Figure 12: **Reward bias ablation.** Mean and 95% CIs of rollout performance across 3 seeds.




Figure 13: **Action scale ablation** Mean and 95% CIs of rollout performance across 3 seeds.

performance using the Cal-QL pre-trained critic is consistently better and is robust to the conservative coefficients α . CQL demonstrates the worst performance with a severe forgetting issue, which aligns with the previous study (Nakamoto et al., 2024).

Update frequency In the SERL pipeline, data collection and policy learning run asynchronously and periodically exchange network parameters and online data. We ablate the *update frequency*—the number of gradient steps performed by the learner between parameter synchronizations with the data-collection actor—sweeping from 1 to 500. As shown in Figure 15, overall performance is largely insensitive to this hyperparameter, indicating robustness across a wide range of synchronization cadences.

On-the-Fly Policy On-the-fly (OTF) policy is introduced in (Dong et al., 2025b) to more effectively maximize the value function. It samples multiple actions and backs up the maximum Q value during TD learning. We adopt OTF to **PLD** while only sampling multiple actions from the residual policy π_δ and conditioned on a fixed base action. We compare different sample sizes in Figure 16. We found that OTF can improve sample efficiency, and a larger sample size (> 20) shows significant performance gain. But empirically, the asymptotic performance will eventually be similar. We use OTF= 1 by default.




Figure 14: **Offline pre-training ablation.** Mean and 95% CIs of rollout performance across 3 seeds.




Figure 15: **Update frequency ablation.** Mean and 95% CIs of rollout performance across 3 seeds.

JSRL We further provide results, including JSRL [Uchendu et al. \(2023\)](#) in Figure 17. We modify the original implementation by opting for a linear scheduler. JSRL demonstrates high data efficiency in general, but could fail to converge on some tasks. While **PLD** can reliably provide solutions for all tasks.

C IMPLEMENTATION DETAILS

C.1 RL ALGORITHM

To ensure apples-to-apples comparisons, all baselines in Section 4.1 and Section B.2 use the same network architecture—an *3-layer MLP Gaussian policy* and *Clipped Double Q-networks (CDQ)* [Fujimoto et al. \(2018\)](#) with *LayerNorm* [\(Ba et al., 2016\)](#). Both actor and critic use a pre-trained ResNetV1-10 encoder to extract visual information. We present a detailed hyperparameter setting in Table 5.




Figure 16: **On-the-fly Policy Ablation.** Mean and 95% CIs of rollout performance across 3 seeds.




Figure 17: **Compared with JSRL.** Mean and 95% CIs of rollout performance across 3 seeds.

Table 5: RL hyperparameter settings. We share the same setting across all tasks.

Hyperparameter	Value
Training	
Batch size	256
Buffer capacity	250000
Discount factor (γ)	0.99
Gradient clipping norm	1.0
Learning rate	3×10^{-4}
Optimizer	AdamW
Reward bias	0.0
Warmup episodes	100
Critic to actor ratio	2
On-the-fly ratio	1
Residual Policy	
Target entropy	$-\frac{act_dim}{2}$
Initial temperature (τ)	1.0
Action scale (ξ)	0.5
Critic	
Q functions ensemble	2
Target update rate	0.005
Architecture	
Visual Encoder	ResNetv1-10
Hidden layer dimension	256
Latent space dimension	256
Q function dropout	0.0
Activation	Tanh
Normalization	LayerNorm

C.2 SFT

For fine-tuning either OpenVLA or π_0 , we employ $8 \times$ NVIDIA L40 GPU for LoRA (Hu et al., 2021) fine-tuning with rank 32. For both π_0 , and OpenVLA-OFT, we use the default hyperparameters from their open-source codebase.

D REAL-WORLD EXPERIMENTS

D.1 EXPERIMENT SETUP

We deploy **PLD** on a 7-DoF Franka Emika Panda with end-effector delta pose control at 20 Hz. The robot is equipped with one wrist-mounted camera, one side-view camera, and proprioceptive sensing as inputs. For each task, we pretrain an independent binary reward classifier by collecting a small-scale dataset of success and failure states. The model structure follows the setup in (Luo et al., 2025), which use a pretrained ResNet-10 and a 3-layer MLP model. We ensure the trained classifier using augmented false positive samples until it achieves 99% success rate for each task. Due to the 3D printed desk, we don't need to reset the environment for the pick-cube task. **PLD**

performs auto-reset, residual RL training, and SFT automatically without human supervision. For the peg-insertion task (depicted in Figure 9), human supervisors need to randomly move the position of the hole to increase diversity.

D.2 GENERALIZATION PERFORMANCE

We perform SFT of π_0 on *Pick Up Blue Cube (Clean Env)* and *Peg Insertion* data, and evaluate the fine-tuned policy on *Pick Up Blue Cube (Cluttered Env)* and *Pick Up Red Cube (Cluttered Env)* tasks. The results in Table 6 show that VLA SFT on **PLD** data achieves better generalization performance compared to human teleoperation data.

Table 6: Comparison of PLD vs Human Data on real-world unseen tasks (success rate).

SR Dataset	PLD Data	Human Data
Pick Up Blue Cube (cluttered Env)	28/30 (93.3%)	12/30 (40.0%)
Pick Up Red Cube (cluttered Env)	20/30 (66.7%)	10/30 (33.3%)
Peg Insertion	30/30 (100.0%)	30/30 (100.0%)